

ZIRKOL CIRCLE PLUS

ZIRKOL – C Plus ist eine Familie von kreisförmigen Hängeleuchten, die sich ideal für die allgemeine und dekorative Beleuchtung von Räumen eignen.

Gehäuse aus eloxiertem Aluminium und Opalschutz für homogene Beleuchtung. CRI > 80

Direkte oder doppelte Lichtemission mit hohem Lichtstrom und mit drei verschiedenen Farbtemperaturen.

Fernspeisung im Lieferumfang.



Ø 1M - DOWNLIGHT - 3000K | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 4000lm |
| Initial luminaire efficacy | 36lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC0310G24WBO
PZRC0310G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 4000lm |
| Initial luminaire efficacy | 36lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1610G24WBO
PZRC1610G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 2000lm + 4000lm |
| Initial luminaire efficacy | 40lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1410G24WBO
PZRC1410G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 2000lm + 4000lm |
| Initial luminaire efficacy | 40lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1710G24WBO
PZRC1710G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 7500lm |
| Initial luminaire efficacy | 68lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC0310G15WBO
PZRC0310G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 7500lm |
| Initial luminaire efficacy | 68lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1610G15WBO
PZRC1610G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 4000lm + 7500lm |
| Initial luminaire efficacy | 77lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1410G15WBO
PZRC1410G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 4000lm + 7500lm |
| Initial luminaire efficacy | 77lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1710G15WBO
PZRC1710G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 5200lm |
| Initial luminaire efficacy | 37lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC0315G24WBO
PZRC0315G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 5200lm |
| Initial luminaire efficacy | 37lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi; shapes, sizes, CCT, RGB, RGBW |
| Customization options | |
| Net lamp weight | 5,4 kg |

Codes

PZRC1615G24WBO
PZRC1615G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 2500lm + 5200lm |
| Initial luminaire efficacy | 38lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1415G24WBO
PZRC1415G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 2500lm + 5200lm |
| Initial luminaire efficacy | 38lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1715G24WBO
PZRC1715G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 9800lm |
| Initial luminaire efficacy | 70lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC0315G15WBO
PZRC0315G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 9800lm |
| Initial luminaire efficacy | 70lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25° |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,5 kg |

Codes

PZRC1615G15WBO
PZRC1615G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 5200lm + 9800lm |
| Initial luminaire efficacy | 75lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1415G15WBO
PZRC1415G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 3000K |
| Luminous flux | 5200lm + 9800lm |
| Initial luminaire efficacy | 75lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,9 kg |

Codes

PZRC1715G15WBO
PZRC1715G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|--|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 7500lm |
| Initial luminaire efficacy | 68lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver ncluded; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC0310G15NBO
PZRC0310G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 110W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 7500lm |
| Initial luminaire efficacy | 68lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1610G15NBO
PZRC1610G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 4000lm + 7500lm |
| Initial luminaire efficacy | 77lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1410G15NBO
PZRC1410G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 150W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 4000lm + 7500lm |
| Initial luminaire efficacy | 77lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø100x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 4 kg |

Codes

PZRC1710G15NBO
PZRC1710G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 9800lm |
| Initial luminaire efficacy | 70lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC0315G15NBO
PZRC0315G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 140W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 9800lm |
| Initial luminaire efficacy | 70lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1615G15NBO
PZRC1615G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

| | |
|---------------------------------|--|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | ON/OFF |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 5200lm + 9800lm |
| Initial luminaire efficacy | 75lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | Ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver interface included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1415G15NBO
PZRC1415G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

| | |
|---------------------------------|---|
| Source | LED strip |
| Total power | 200W |
| Emission | diffused orientable |
| Switching | DALI |
| Tension | 24VDC |
| Color temperature | 4000K |
| Luminous flux | 5200lm + 9800lm |
| Initial luminaire efficacy | 75lm/W |
| Initial chromaticity | SDCM<3 |
| Typ CRI | > 80 |
| IP class | 40 |
| Dimensions | ø150x2,6x5cm |
| Materials | aluminium |
| Ambient temperature range | 0°C / +35°C |
| Performance ambient temperature | 25°C |
| Notes | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options | shapes, sizes, CCT, RGB, RGBW |
| Net lamp weight | 5,4 kg |

Codes

PZRC1715G15NBO
PZRC1715G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |