

# SLACKLINE TRIM

Die SLACKLINE-Familie besteht aus einer großen Auswahl an Aluminiumprofilen mit unterschiedlichen Befestigungen mit derselben LED-LEuchtmittel, die die Slackline-Installation in jedem Ambiente sehr flexibel macht: Slackline Trim, Slackline Regular und Slackline Micro.


Minimales Design mit hoher Lichtqualität.

Slackline eignet sich für lineare Verbindungslösungen (auf Anfrage).

Je nach Befestigung wird es in unterschiedlichen Standardlängen mit CRI > 94 angeboten.



1M | 3000K



### LAMPING

Source	LED strip
Total power	15W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	560lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM <
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,3x2x100,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg

### Codes

BSLA0110G26WAA

### Structure

grey

### PACKAGE


Package 01

Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

### Certificazioni



1M | 4000K



### LAMPING

Source	LED strip
Total power	15W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	660lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x100,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg

### Codes

BSLA0110G26NAA

### Structure

grey

### PACKAGE


Package 01

Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

### Certificazioni



2M | 3000K



### LAMPING

Source	LED strip
Total power	30W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1120lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM <3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,3x2x200cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg

### Codes

BSLA0120G26WAA

### Structure

grey

### PACKAGE


Package 01

Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

### Certificazioni



2M | 4000K



### LAMPING

Source	LED strip
Total power	30W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1320lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x200cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg

### Codes

BSLA0120G26NAA

### Structure

grey


### PACKAGE

Package 01 Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

### Certificazioni



3M | 3000K



### LAMPING

Source	LED strip
Total power	45W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1980lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM <3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,3x2x299,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	1,32 kg

### Codes

BSLA0130G26WAA

### Structure

grey


### PACKAGE

Package 01 Dimension: 305x11x2,5 cm / Gross weight: 1,32 kg

### Certificazioni



3M | 4000K



### LAMPING

Source	LED strip
Total power	45W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1680lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x299,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface,   Recessed fix kit for plasterboard,
Net lamp weight	1,32 kg

### Codes

BSLA0130G26NAA

### Structure

grey

### PACKAGE

Package 01

Dimension: 305x11x2,5 cm / Gross weight: 1,32 kg

### Certificazioni

