

LIPARI

Famille de spots encastrés downlight pour éclairage d'accentuation en intérieur. L'appareil peut être orienté à 30° verticalement et à 355° horizontalement pour diriger la lumière selon votre désir. La structure modulaire sépare la lampe en plusieurs parties indépendantes. Les anneaux externes avec diverses finitions sont faciles à monter et peuvent être facilement remplacés pour satisfaire les exigences diverses d'ouverture et les effets esthétiques. Lipari est disponible avec plusieurs accessoires d'optique pour satisfaire les différents besoins d'éclairage.



RECESSED TRIMLESS 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW2 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m
Accessories	Drivers, Lipari Lipari ring, Lipari ring
Net lamp weight	0,92 kg

Codes

LIP LW3 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW2 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m
Accessories	Drivers, Lipari Lipari ring, Lipari ring
Net lamp weight	0,92 kg

Codes

LIP LW3 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	Ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 61
LIT LN2 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 61
LIT LN3 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 63
LIT LN2 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 63
LIT LN3 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg

Certificazioni



TRIMLESS



TRIM

