

ZIRKOL TRACK UGR

Die neue Leuchte der Kollektion, Zirkol Linear Track UGR, ist mit einer speziellen optischen Gruppe ausgestattet, die eine direkte Beleuchtung mit einem reduzierten Blendungsindex (UGR < 19) ermöglicht und besonders für den Einsatz in Büros und an Arbeitsplätzen geeignet ist, an denen ein hoher Sehkomfort erforderlich ist. Das Aluminiumprofil ist in weißer und schwarzer Ausführung und mit LED-Farbtemperaturen von 3000K und 4000K erhältlich. Die Zirkol Linear Track UGR ist mit den 3 Phasen Stromschienen kompatibel. Eingebauter Treiber.



0,84M | 3000M

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2160lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	



Codes

BZRL54084I42NBO
BZRL54084I42NNE

Structure

white
black

Certificazioni



1,15M | 3000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2957lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54115I42NBO
BZRL54115I42NNE

Structure

white
black

Certificazioni



0,84M | 4000K

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2220lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	



Codes

BZRL54084I42WBO
BZRL54084I42WNE

Structure

white
black

Certificazioni



1,15M | 4000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	3039lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5,10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	

Codes

BZRL54115I42WBO
BZRL54115I42WNE

Structure

white
black

Certificazioni

