

ZIRKOL CIRCLE UGR

Zirkol Circle UGR ist eine Familie von kreisförmigen Hängeleuchten, die sich ideal für die allgemeine und dekorative Beleuchtung von Räumen eignen.

Gehäuse aus eloxiertem Aluminium und Downlight in UGR<19-Optik.

Erhältlich mit direkter oder doppelter Lichtemission und drei verschiedenen Farbtemperaturen.

Fernnetzgerät und dimmer-Modul im Lieferumfang enthalten.



1M | DOWNLIGHT - 2700K

LAMPING

Source	flex LED strip 30°
Total power	59W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	2700K
Luminous flux	3505lm
Initial luminaire efficacy	59lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,3 kg

Codes

BZRC1610I42DNE

Structure

black

PACKAGE




Package 01

Dimension: 115x115x12 cm / Gross weight: 7,08 kg

Certificazioni



ZIRKOL CIRCLE UGR



1M | DOWNLIGHT - 3000K

LAMPING

Source	flex LED strip 30°
Total power	59W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	3894lm
Initial luminaire efficacy	66lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,30 kg

Codes

BZRC1610I42WNE

Structure

black

PACKAGE




Package 01

Dimension: 115x115x12 cm / Gross weight: 7,08 kg

Certificazioni



ZIRKOL CIRCLE UGR



1M | DOWNLIGHT - 4000K

LAMPING

Source	flex LED strip 30°
Total power	59W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	4327lm
Initial luminaire efficacy	73lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,3 kg

Codes

BZRC1610I42NNE

Structure

black

PACKAGE




Package 01

Dimension: 115x115x12 cm / Gross weight: 7,08 kg

Certificazioni



ZIRKOL CIRCLE UGR



1M | UP-DOWNLIGHT - 2700K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	104W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	2700K
Luminous flux	5646lm
Initial luminaire efficacy	54lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,4 kg

Codes

BZRC1710I42DNE

Structure

black

PACKAGE




Package 01

Dimension: 115x115x12 cm / Gross weight: 7,2 kg

Certificazioni



ZIRKOL CIRCLE UGR



1M | UP-DOWNLIGHT - 3000K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	104W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	6274lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,4 kg

Codes

BZRC1710I42WNE

Structure

black

PACKAGE




Package 01

Dimension: 115x115x12 cm / Gross weight: 7,2 kg

Certificazioni



ZIRKOL CIRCLE UGR



1M | UP-DOWNLIGHT - 4000K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	104W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	6971lm
Initial luminaire efficacy	67lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø99,5x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	4,4 kg

Codes

BZRC1710I42NNE

Structure

black

PACKAGE



Package 01

Dimension: 115x115x12 cm / Gross weight: 7,2 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | DOWNLIGHT - 2700K

LAMPING

Source	flex LED strip 30°
Total power	70W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	2700K
Luminous flux	4130lm
Initial luminaire efficacy	59lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,02 kg

Codes

BZRC1612I42DNE

Structure

black

PACKAGE




Package 01

Dimension: 165x165x12 cm / Gross weight: 9,8 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | DOWNLIGHT - 3000K

LAMPING

Source	flex LED strip 30°
Total power	70W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	4620lm
Initial luminaire efficacy	66lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,02 kg

Codes

BZRC1612I42WNE

Structure

black

PACKAGE




Package 01

Dimension: 165x165x12 cm / Gross weight: 9,8 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | DOWNLIGHT - 4000K

LAMPING

Source	flex LED strip 30°
Total power	70W
Emission	UGR<19
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	5110lm
Initial luminaire efficacy	73lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 75W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,02 kg

Codes

BZRC1612I42NNE

Structure

black

PACKAGE




Package 01

Dimension: 165x165x12 cm / Gross weight: 9,8 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | UP-DOWNLIGHT - 2700K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	124W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	2700K
Luminous flux	6696lm
Initial luminaire efficacy	54lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,14 kg

Codes

BZRC1712I42DNE

Structure

black

PACKAGE




Package 01

Dimension: 165x165x12 cm / Gross weight: 9,9 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | UP-DOWNLIGHT - 3000K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	124W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7440lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,14 kg

Codes

BZRC1712I42WNE

Structure

black

PACKAGE




Package 01

Dimension: 165x165x12 cm / Gross weight: 9,9 kg

Certificazioni



ZIRKOL CIRCLE UGR



1,2M | UP-DOWNLIGHT - 4000K

LAMPING

Source	flex LED strip 30° + LED strip
Total power	124W
Emission	UGR<19 + diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	8308lm
Initial luminaire efficacy	67lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø118,8x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	1 x driver 150W (110/240V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included RAL 9005 black shipped assembled
Net lamp weight	5,14 kg

Codes

BZRC1712I42NNE

Structure

black

PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 9,9 kg

Certificazioni



ZIRKOL CIRCLE UGR

