

SLACKLINE TRIM

SLACKLINE family is composed of a wide selection of aluminium profiles with different fixing types but with the same LED source: Slackline Trim, Slackline Regular and Slackline Micro. These characteristics make the Slackline installation very flexible in any ambience.


Minimal design and excellent light quality.

Slackline is also suitable for linear connection solutions (on request).

Depending on fixing types, the Slackline comes in various different standard lengths with CRI>94.



1M | 3000K



LAMPING

Source	LED strip
Total power	15W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	560lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,25x2x100,5cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg

Codes

BSLA0110G26WAA

Structure

grey

PACKAGE


Package 01

Dimension: 105x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



1M | 4000K



LAMPING

Source	LED strip
Total power	15W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	660lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,25x2x100,5cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg

Codes

BSLA0110G26NAA

Structure

grey

PACKAGE


Package 01

Dimension: 105x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



2M | 3000K



LAMPING

Source	LED strip
Total power	30W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1120lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,25x2x200cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg

Codes

BSLA0120G26WAA

Structure

grey


PACKAGE

Package 01 Dimension: 205x11x2,5 cm / Gross weight: 1,32 kg

Certificazioni



2M | 4000K



LAMPING

Source	LED strip
Total power	30W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1320lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,25x2x200cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg

Codes

BSLA0120G26NAA

Structure

grey


PACKAGE

Package 01 Dimension: 205x11x2,5 cm / Gross weight: 1,32 kg

Certificazioni



3M | 3000K



LAMPING

Source	LED strip
Total power	45W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1980lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,25x2x299,5cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	1,32 kg

Codes

BSLA0130G26WAA

Structure

grey

PACKAGE


Package 01

Dimension: 305x11x2,5 cm / Gross weight: 1,74 kg

Certificazioni



3M | 4000K



LAMPING

Source	LED strip
Total power	45W
Emission	Diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1680lm
Initial luminaire efficacy	> 37lm/W
Initial chromaticity	SDCM < 3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,25x2x299,5cm
Materials	Anodized aluminum
Ambient temperature range	- 20°C / 35°
Performance ambient temperature	25°
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	1,32 kg

Codes

BSLA0130G26NAA

Structure

grey

PACKAGE

Package 01 Dimension: 305x11x2,5 cm / Gross weight: 1,74 kg

Certificazioni

