

FLEX CEILING

FLEX is a family of miniaturized adjustable spots dedicated to accent lighting.

Available in numerous fixings, optics and finishes to fulfil any installation requirement. The FLEX Collection is composed of FLEX CEILING with a fixed and variable optic, different beam angles and in black, gold, anodized grey and bronze grey finish. The integrated aluminium joint allows fixation and orientation without any visible cable.



FIXED OPTIC | 3000K - 20°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 20°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21WAN
BFLE0401F21WAO
BFLE0401F21WAA
BFLE0401F21WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 3000K - 30°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 30°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421WAN
BFLE0401421WAO
BFLE0401421WAA
BFLE0401421WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 20°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 20°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21NAN
BFLE0401F21NAO
BFLE0401F21NAA
BFLE0401F21NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 30°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 30°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421NAN
BFLE0401421NAO
BFLE0401421NAA
BFLE0401421NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 3000K

LAMPING

Source	LED
Total power	4,2W
Emission	direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	76lm (45°)
Initial luminaire efficacy	18lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x10,7cm
Materials	anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included, orientable spot $\pm 42^\circ$, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401921WAN

Structure

black

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 4000K

LAMPING

Source	LED
Total power	4,2W
Emission	direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	80lm (45°)
Initial luminaire efficacy	19lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x10,7cm
Materials	anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,10 kg

Codes

BFLE0401921NAN

Structure

black

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,14 kg

Certificazioni



FIXED OPTIC



ZOOM OPTIC

