

*Massimo Colagrande*

# PLINT BATTERY MINI

ILTI Luce's exploration of the world of architectural battery-powered lighting proceeds with an innovative design path that began with Plint. After reversing the accent lighting paradigm, ILTI Luce's miniaturization ability is revealed in its highly flexible reduced version. Inside a metal structure, a high-performance spot is powered by a highly flexible battery for accent lighting. Dimmer on board.



## 3000K

### LAMPING

|                            |   |
|----------------------------|---|
| Source                     | LED   |
| Total power                | 2,4W  |
| Emission                   | direct 14°  |
| Switching                  | on board  |
| Tension                    | 5V  |
| Color temperature          | 3000K   |
| Luminous flux              | 185lm   |
| Initial luminaire efficacy | 77lm/W  |
| Typ CRI                    | 90  |
| Energy class               | G   |
| IP class                   | 20  |
| Dimensions                 | 13x11,6   |
| Notes                      | cable included (USB-C), rechargeable, 5 hours battery life, 4,5 hours charge time (light off) |
| Net lamp weight            | 0,55 kg   |

### Codes

PLM BNN 11  
PLM BWN 11  
PLM BON 11  
PLM BDN 11

### Structure

black  
white  
gold  
silver

### PACKAGE

Package 01 Dimension: 19x19x8 cm / Gross weight: 0,70 kg

### Certificazioni

