

# ZIRKOL CIRCLE PLUS

ZIRKOL – C Plus est une famille de circulaire luminaires suspendus idéale pour l'éclairage général et décoratif.

Corps en aluminium anodisé et écran de protection opale pour un éclairage homogène. IRC > 80. L'émission de la lumière peut être directe ou directe/indirecte avec un haut flux lumineux et trois différentes températures de couleur. Alimentation déportée incluse.



## Ø 1M - DOWNLIGHT - 3000K | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 110W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 4000lm                                                                                              |
| Initial luminaire efficacy      | 36lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 4 kg                                                                                                |

### Codes

PZRC0310G24WBO  
PZRC0310G24WNE


### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - DOWNLIGHT - 3000K | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 110W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 4000lm                                                                                                              |
| Initial luminaire efficacy      | 36lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 4 kg                                                                                                                |

### Codes

PZRC1610G24WBO  
PZRC1610G24WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K | ON-OFF

LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 150W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 2000lm + 4000lm                                                                                     |
| Initial luminaire efficacy      | 40lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | ø100x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 4 kg                                                                                                |

Codes

PZRC1410G24WBO  
PZRC1410G24WNE


Structure

white  
black

PACKAGE

Package 01                      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

## Ø 1M - UP-DOWNLIGHT - 3000K | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 150W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 2000lm + 4000lm                                                                                                     |
| Initial luminaire efficacy      | 40lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 4 kg                                                                                                                |

### Codes

PZRC1710G24WBO  
PZRC1710G24WNE


### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 110W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 7500lm                                                                                              |
| Initial luminaire efficacy      | 68lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 4 kg                                                                                                |

### Codes

PZRC0310G15WBO  
PZRC0310G15WNE


### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                                                      |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                                            |
| Total power                     | 110W                                                                                                                                                 |
| Emission                        | diffused orientable                                                                                                                                  |
| Switching                       | DALI                                                                                                                                                 |
| Tension                         | 24VDC                                                                                                                                                |
| Color temperature               | 3000K                                                                                                                                                |
| Luminous flux                   | 7500lm                                                                                                                                               |
| Initial luminaire efficacy      | 68lm/W                                                                                                                                               |
| Initial chromaticity            | SDCM<3                                                                                                                                               |
| Typ CRI                         | > 80                                                                                                                                                 |
| IP class                        | 40                                                                                                                                                   |
| Dimensions                      | Ø100x2,6x5cm                                                                                                                                         |
| Materials                       | aluminium                                                                                                                                            |
| Ambient temperature range       | 0°C / +35°C                                                                                                                                          |
| Performance ambient temperature | 25°C                                                                                                                                                 |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi<br>shapes, sizes, CCT, RGB, RGBW |
| Customization options           |                                                                                                                                                      |
| Net lamp weight                 | 4 kg                                                                                                                                                 |

### Codes

PZRC1610G15WBO  
PZRC1610G15WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 150W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 4000lm + 7500lm                                                                                     |
| Initial luminaire efficacy      | 77lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 4 kg                                                                                                |

### Codes

PZRC1410G15WBO  
PZRC1410G15WNE

### Structure

white  
black

### PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 150W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 4000lm + 7500lm                                                                                                     |
| Initial luminaire efficacy      | 77lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 4 kg                                                                                                                |

### Codes

PZRC1710G15WBO  
PZRC1710G15WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 3000K | ON-OFF

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 140W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | ON/OFF                                                                                                              |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 5200lm                                                                                                              |
| Initial luminaire efficacy      | 37lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø150x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                                              |

### Codes

PZRC0315G24WBO  
PZRC0315G24WNE


### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 3000K | DALI

### LAMPING

|                                 |                                                                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                                             |
| Total power                     | 140W                                                                                                                                                  |
| Emission                        | diffused orientable                                                                                                                                   |
| Switching                       | DALI                                                                                                                                                  |
| Tension                         | 24VDC                                                                                                                                                 |
| Color temperature               | 3000K                                                                                                                                                 |
| Luminous flux                   | 5200lm                                                                                                                                                |
| Initial luminaire efficacy      | 37lm/W                                                                                                                                                |
| Initial chromaticity            | SDCM<3                                                                                                                                                |
| Typ CRI                         | > 80                                                                                                                                                  |
| IP class                        | 40                                                                                                                                                    |
| Dimensions                      | ø150x2,6x5cm                                                                                                                                          |
| Materials                       | aluminium                                                                                                                                             |
| Ambient temperature range       | 0°C / +35°C                                                                                                                                           |
| Performance ambient temperature | 25°C                                                                                                                                                  |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi;<br>shapes, sizes, CCT, RGB, RGBW |
| Customization options           |                                                                                                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                                                                                |

### Codes

PZRC1615G24WBO  
PZRC1615G24WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 3000K | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 200W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 2500lm + 5200lm                                                                                     |
| Initial luminaire efficacy      | 38lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø150x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                              |

### Codes

PZRC1415G24WBO  
PZRC1415G24WNE

### Structure

white  
black

### PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 3000K | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 200W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 2500lm + 5200lm                                                                                                     |
| Initial luminaire efficacy      | 38lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | ø150x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                                              |

### Codes

PZRC1715G24WBO  
PZRC1715G24WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 140W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 9800lm                                                                                              |
| Initial luminaire efficacy      | 70lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | ø150x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                              |

### Codes

PZRC0315G15WBO  
PZRC0315G15WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 140W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 9800lm                                                                                                              |
| Initial luminaire efficacy      | 70lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | ø150x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°                                                                                                                 |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 5,5 kg                                                                                                              |

### Codes

PZRC1615G15WBO  
PZRC1615G15WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 200W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 5200lm + 9800lm                                                                                     |
| Initial luminaire efficacy      | 75lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø150x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                              |

### Codes

PZRC1415G15WBO  
PZRC1415G15WNE

### Structure

white  
black

### PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 200W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 3000K                                                                                                               |
| Luminous flux                   | 5200lm + 9800lm                                                                                                     |
| Initial luminaire efficacy      | 75lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø150x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 5,9 kg                                                                                                              |

### Codes

PZRC1715G15WBO  
PZRC1715G15WNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                    |
|---------------------------------|----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                          |
| Total power                     | 110W                                                                                               |
| Emission                        | diffused orientable                                                                                |
| Switching                       | ON/OFF                                                                                             |
| Tension                         | 24VDC                                                                                              |
| Color temperature               | 4000K                                                                                              |
| Luminous flux                   | 7500lm                                                                                             |
| Initial luminaire efficacy      | 68lm/W                                                                                             |
| Initial chromaticity            | SDCM<3                                                                                             |
| Typ CRI                         | > 80                                                                                               |
| IP class                        | 40                                                                                                 |
| Dimensions                      | Ø100x2,6x5cm                                                                                       |
| Materials                       | aluminium                                                                                          |
| Ambient temperature range       | 0°C / +35°C                                                                                        |
| Performance ambient temperature | 25°C                                                                                               |
| Notes                           | remote driver ncluded; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                      |
| Net lamp weight                 | 4 kg                                                                                               |

### Codes

PZRC0310G15NBO  
PZRC0310G15NNE

### Structure


white  
black

### PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 110W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 4000K                                                                                                               |
| Luminous flux                   | 7500lm                                                                                                              |
| Initial luminaire efficacy      | 68lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 4 kg                                                                                                                |

### Codes

PZRC1610G15NBO  
PZRC1610G15NNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 150W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 4000lm + 7500lm                                                                                     |
| Initial luminaire efficacy      | 77lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | Ø100x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 4 kg                                                                                                |

### Codes

PZRC1410G15NBO  
PZRC1410G15NNE

### Structure

white  
black

### PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                                                      |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                                            |
| Total power                     | 150W                                                                                                                                                 |
| Emission                        | diffused orientable                                                                                                                                  |
| Switching                       | DALI                                                                                                                                                 |
| Tension                         | 24VDC                                                                                                                                                |
| Color temperature               | 4000K                                                                                                                                                |
| Luminous flux                   | 4000lm + 7500lm                                                                                                                                      |
| Initial luminaire efficacy      | 77lm/W                                                                                                                                               |
| Initial chromaticity            | SDCM<3                                                                                                                                               |
| Typ CRI                         | > 80                                                                                                                                                 |
| IP class                        | 40                                                                                                                                                   |
| Dimensions                      | Ø100x2,6x5cm                                                                                                                                         |
| Materials                       | aluminium                                                                                                                                            |
| Ambient temperature range       | 0°C / +35°C                                                                                                                                          |
| Performance ambient temperature | 25°C                                                                                                                                                 |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi<br>shapes, sizes, CCT, RGB, RGBW |
| Customization options           |                                                                                                                                                      |
| Net lamp weight                 | 4 kg                                                                                                                                                 |

### Codes

PZRC1710G15NBO  
PZRC1710G15NNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 115x115x12 cm / Gross weight: 6,5 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                           |
| Total power                     | 140W                                                                                                |
| Emission                        | diffused orientable                                                                                 |
| Switching                       | ON/OFF                                                                                              |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 9800lm                                                                                              |
| Initial luminaire efficacy      | 70lm/W                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | ø150x2,6x5cm                                                                                        |
| Materials                       | aluminium                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                         |
| Performance ambient temperature | 25°C                                                                                                |
| Notes                           | remote driver included; suspension kit included;<br>cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                              |

### Codes

PZRC0315G15NBO  
PZRC0315G15NNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

### LAMPING

|                                 |                                                                                                                     |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                           |
| Total power                     | 140W                                                                                                                |
| Emission                        | diffused orientable                                                                                                 |
| Switching                       | DALI                                                                                                                |
| Tension                         | 24VDC                                                                                                               |
| Color temperature               | 4000K                                                                                                               |
| Luminous flux                   | 9800lm                                                                                                              |
| Initial luminaire efficacy      | 70lm/W                                                                                                              |
| Initial chromaticity            | SDCM<3                                                                                                              |
| Typ CRI                         | > 80                                                                                                                |
| IP class                        | 40                                                                                                                  |
| Dimensions                      | ø150x2,6x5cm                                                                                                        |
| Materials                       | aluminium                                                                                                           |
| Ambient temperature range       | 0°C / +35°C                                                                                                         |
| Performance ambient temperature | 25°C                                                                                                                |
| Notes                           | remote driver and DALI interface included;<br>suspension kit included; cable 5m; optional<br>controls: DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                                       |
| Net lamp weight                 | 5,4 kg                                                                                                              |

### Codes

PZRC1615G15NBO  
PZRC1615G15NNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

### LAMPING

|                                 |                                                                                                            |
|---------------------------------|------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                  |
| Total power                     | 200W                                                                                                       |
| Emission                        | diffused orientable                                                                                        |
| Switching                       | ON/OFF                                                                                                     |
| Tension                         | 24VDC                                                                                                      |
| Color temperature               | 4000K                                                                                                      |
| Luminous flux                   | 5200lm + 9800lm                                                                                            |
| Initial luminaire efficacy      | 75lm/W                                                                                                     |
| Initial chromaticity            | SDCM<3                                                                                                     |
| Typ CRI                         | > 80                                                                                                       |
| IP class                        | 40                                                                                                         |
| Dimensions                      | Ø150x2,6x5cm                                                                                               |
| Materials                       | aluminium                                                                                                  |
| Ambient temperature range       | 0°C / +35°C                                                                                                |
| Performance ambient temperature | 25°C                                                                                                       |
| Notes                           | remote driver interface included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi |
| Customization options           | shapes, sizes, CCT, RGB, RGBW                                                                              |
| Net lamp weight                 | 5,4 kg                                                                                                     |

### Codes

PZRC1415G15NBO  
PZRC1415G15NNE

### Structure

white  
black

### PACKAGE

Package 01      Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |

## Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

### LAMPING

|                                 |                     |
|---------------------------------|---------------------|
| Source                          | LED strip           |
| Total power                     | 200W                |
| Emission                        | diffused orientable |
| Switching                       | DALI                |
| Tension                         | 24VDC               |
| Color temperature               | 4000K               |
| Luminous flux                   | 5200lm + 9800lm     |
| Initial luminaire efficacy      | 75lm/W              |
| Initial chromaticity            | SDCM<3              |
| Typ CRI                         | > 80                |
| IP class                        | 40                  |
| Dimensions                      | ø150x2,6x5cm        |
| Materials                       | aluminium           |
| Ambient temperature range       | 0°C / +35°C         |
| Performance ambient temperature | 25°C                |
| Notes                           |                     |

Customization options  
Net lamp weight

remote driver and DALI interface included;  
suspension kit included; cable 5m; optional  
controls: DMX, Casambi  
shapes, sizes, CCT, RGB, RGBW  
5,4 kg

### Codes

PZRC1715G15NBO  
PZRC1715G15NNE

### Structure

white  
black

### PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

### Certificazioni



| Ø100/150 |