

SLACKLINE TRIM

La famille SLACKLINE est composé d'une ample sélection de profilés en aluminium avec différents types de fixation, dotés de la même source lumineuse: Slackline Trim, Slackline Regular et Slackline Micro. Ces caractéristiques rendent l'utilisation du Slackline très flexible pour chaque contexte. Design minimal et grande qualité de la lumière. Slackline représente la solution idéale pour réaliser une ligne continue (sur demande). Selon le type de montage, diverses longueurs standard sont disponibles et avec un IRC>94.



1M | 3000K

LAMPING

Source	LED strip
Total power	15W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	560lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM <
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,3x2x100,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg


Codes

BSLA0110G26WAA

PACKAGE

Package 01 Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

Certificazioni



1M | 4000K

LAMPING

Source	LED strip
Total power	15W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	660lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x100,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,45 kg


Codes

BSLA0110G26NAA

PACKAGE

Package 01 Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

Certificazioni



2M | 3000K

LAMPING

Source	LED strip
Total power	30W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1120lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM <3
Typ CRI	97
Energy class	F
IP class	40
Dimensions	3,3x2x200cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg


Codes

BSLA0120G26WAA

PACKAGE

Package 01 Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



2M | 4000K

LAMPING

Source	LED strip
Total power	30W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1320lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x200cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	0,87 kg


Codes

BSLA0120G26NAA

PACKAGE

Package 01 Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



CE UKCA

3M | 4000K

LAMPING

Source	LED strip
Total power	45W
Emission	diffused
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1680lm
Initial luminaire efficacy	44lm/W
Initial chromaticity	SDCM <3
Typ CRI	94
Energy class	E
IP class	40
Dimensions	3,3x2x299,5cm
Materials	anodized aluminum
Ambient temperature range	- 20°C / 35°C
Performance ambient temperature	25°C
Notes	driver not included, cable length 0,5m, Wooden fixing clip included
Customization options	CCT 2700K, body length
Accessories	Drivers 24VDC + DALI interface, Recessed fix kit for plasterboard,
Net lamp weight	1,32 kg

Codes

BSLA0130G26NAA

PACKAGE

Package 01 Dimension: 305x11x2,5 cm / Gross weight: 1,32 kg

Certificazioni

