

ZIRKOL LINEAR CEILING

Le Zirkol Linear Ceiling est réalisé avec un profil linéaire en aluminium proposé dans les finitions noir, blanc et or mat. Il est complété par une vasque opale pour un éclairage direct et homogène, avec des températures de couleur LED de 2700K, 3000K ou 4000K. Driver intégré.



1M CEILING | 2700K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	1900lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	E
IP class	40
Dimensions	100x2,6x5
Materials	aluminum
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRLU410G15DBO
BZRLU410G15DNE
BZRLU410G15DOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M CEILING | 3000K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2000lm
Initial luminaire efficacy	71lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	E
IP class	40
Dimensions	100x2,6x5
Materials	aluminum
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRLU410G15WBO
BZRLU410G15WNE
BZRLU410G15WOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M CEILING | 4000K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2100lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	D
IP class	40
Dimensions	100x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRLU410G15NBO
BZRLU410G15NNE
BZRLU410G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



2M CEILING | 2700K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	3800lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	E
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRLU420G15DBO
BZRLU420G15DNE
BZRLU420G15DOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



2M CEILING | 3000K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	4000lm
Initial luminaire efficacy	71lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	E
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRLU420G15WBO
BZRLU420G15WNE
BZRLU420G15WOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



2M CEILING | 4000K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	4200lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	D
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRLU420G15NBO
BZRLU420G15NNE
BZRLU420G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni

