

ZIRKOL LINEAR CEILING UGR

La nouvelle lampe de la collection, Zirkol Linear UGR est équipée d'un groupe optique particulier qui permet un éclairage direct avec un indice d'éblouissement réduit (UGR <19). Profilé en aluminium disponible dans les finitions blanc et noir et avec des températures de couleur LED de 3000K et 4000K. Zirkol Linear UGR est maintenant présenté dans la version Ceiling, avec driver intégré et est particulièrement adapté à une application dans les bureaux et les environnements de travail, où un confort visuel élevé est requis.



1,4M CEILING | 3000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	3000K
Luminous flux	3600lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42WBO
BZRLU414I42WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni



1,4M CEILING | 4000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	4000K
Luminous flux	3700lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42NBO
BZRLU414I42NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni

