

ZIRKOL LINEAR WALL

Dédié à l'éclairage indirect et à forte connotation décorative, Zirkol Linear Wall est la nouvelle lampe de la collection, proposée avec une forme linéaire et une fixation murale. Trois températures de couleur LED disponibles, 2700K, 3000K ou 4000K et finitions noire, blanc et l'or.



1M | 2700K

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	833lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15DBO
BZRL4010G15DNE
BZRL4010G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



ZIRKOL LINEAR WALL



1M | 3000K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	882lm
Initial luminaire efficacy	61lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15WBO
BZRL4010G15WNE
BZRL4010G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M | 4000K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	980lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15NBO
BZRL4010G15NNE
BZRL4010G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



2M | 2700K

LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	1666lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15DBO
BZRL4020G15DNE
BZRL4020G15DOR


Structure

white
black
gold

PACKAGE

Package 01	Dimension: 250x11x11 cm / Gross weight: 4,69 kg
------------	---

Certificazioni



ZIRKOL LINEAR WALL



LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	1764lm
Initial luminaire efficacy	61lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15WBO
BZRL4020G15WNE
BZRL4020G15WOR

Structure

white
black
gold

PACKAGE

Package 01	Dimension: 250x11x11 cm / Gross weight: 4,69 kg
------------	---

Certificazioni



2M | 4000K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	1960lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15NBO
BZRL4020G15NNE
BZRL4020G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni

