

# SLACKLINE TRIM

La famiglia SLACKLINE è composta da un'ampia selezione di profili in alluminio con differenti tipologie di fissaggio, dotati della stessa sorgente LED: Slackline Trim, Slackline Regular e Slackline Micro. Queste caratteristiche rendono l'impiego di Slackline molto flessibile in ogni ambiente.

Design minimal ed elevata qualità della luce.

Slackline rappresenta la soluzione ideale per realizzare soluzioni in linea continua (su richiesta).

A seconda del tipo di fissaggio, è proposto in differenti lunghezze standard e con CRI>94.



1M | 3000K

LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 15W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 3000K                                                                   |
| Luminous flux                   | 560lm                                                                   |
| Initial luminaire efficacy      | 37lm/W                                                                  |
| Initial chromaticity            | SDCM <                                                                  |
| Typ CRI                         | 97                                                                      |
| Energy class                    | F                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x100,5cm                                                           |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 0,45 kg                                                                 |


Codes

BSLA0110G26WAA

PACKAGE

Package 01                      Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

Certificazioni



1M | 4000K

### LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 15W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 4000K                                                                   |
| Luminous flux                   | 660lm                                                                   |
| Initial luminaire efficacy      | 44lm/W                                                                  |
| Initial chromaticity            | SDCM <3                                                                 |
| Typ CRI                         | 94                                                                      |
| Energy class                    | E                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x100,5cm                                                           |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 0,45 kg                                                                 |

### Codes

BSLA0110G26NAA


### PACKAGE

Package 01

### Structure

grey

### Certificazioni



2M | 3000K

LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 30W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 3000K                                                                   |
| Luminous flux                   | 1120lm                                                                  |
| Initial luminaire efficacy      | 37lm/W                                                                  |
| Initial chromaticity            | SDCM <3                                                                 |
| Typ CRI                         | 97                                                                      |
| Energy class                    | F                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x200cm                                                             |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 0,87 kg                                                                 |

Codes

BSLA0120G26WAA

PACKAGE

Package 01      Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



2M | 4000K

LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 30W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 4000K                                                                   |
| Luminous flux                   | 1320lm                                                                  |
| Initial luminaire efficacy      | 44lm/W                                                                  |
| Initial chromaticity            | SDCM <3                                                                 |
| Typ CRI                         | 94                                                                      |
| Energy class                    | E                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x200cm                                                             |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 0,87 kg                                                                 |


Codes

BSLA0120G26NAA

PACKAGE

Package 01                      Dimension: 205x11x2,5 cm / Gross weight: 0,87 kg

Certificazioni



3M | 3000K

LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 45W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 3000K                                                                   |
| Luminous flux                   | 1980lm                                                                  |
| Initial luminaire efficacy      | 37lm/W                                                                  |
| Initial chromaticity            | SDCM <3                                                                 |
| Typ CRI                         | 97                                                                      |
| Energy class                    | F                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x299,5cm                                                           |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 1,32 kg                                                                 |

Codes

BSLA0130G26WAA

PACKAGE

Package 01                      Dimension: 305x11x2,5 cm / Gross weight: 1,32 kg

Certificazioni



3M | 4000K

LAMPING

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Source                          | LED strip                                                               |
| Total power                     | 45W                                                                     |
| Emission                        | diffused                                                                |
| Switching                       | according to driver                                                     |
| Tension                         | 24VDC                                                                   |
| Color temperature               | 4000K                                                                   |
| Luminous flux                   | 1680lm                                                                  |
| Initial luminaire efficacy      | 44lm/W                                                                  |
| Initial chromaticity            | SDCM <3                                                                 |
| Typ CRI                         | 94                                                                      |
| Energy class                    | E                                                                       |
| IP class                        | 40                                                                      |
| Dimensions                      | 3,3x2x299,5cm                                                           |
| Materials                       | anodized aluminum                                                       |
| Ambient temperature range       | - 20°C / 35°C                                                           |
| Performance ambient temperature | 25°C                                                                    |
| Notes                           | driver not included, cable length 0,5m, Wooden<br>fixing clip included  |
| Customization options           | CCT 2700K, body length                                                  |
| Accessories                     | Drivers 24VDC + DALI interface,   Recessed fix kit<br>for plasterboard, |
| Net lamp weight                 | 1,32 kg                                                                 |

Codes

BSLA0130G26NAA

PACKAGE

Package 01                      Dimension: 305x11x2,5 cm / Gross weight: 1,32 kg

Certificazioni

