

LIPARI

Famiglia di faretti da incasso downlight per illuminazione d'accento in interni. L'apparecchio può essere ruotato di 30 ° in verticale e ruotato di 355 ° a livello orizzontale, per orientare la luce a piacere. La struttura modulare separa la lampada in più parti indipendenti. Gli anelli esterni con diverse finiture sono semplici da montare e possono essere facilmente sostituiti per soddisfare le diverse esigenze di apertura ed effetti estetici.

Lipari è proposto con diverse ottiche accessorie, per soddisfare differenti necessità di illuminazione.



RECESSED TRIMLESS 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW2 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m
Accessories	Drivers, Lipari Lipari ring, Lipari ring
Net lamp weight	0,92 kg

Codes

LIP LW3 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW2 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW3 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	Ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 61
LIT LN2 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 61
LIT LN3 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 63
LIT LN2 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
Energy class	F
IP class	20
Dimensions	Ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Accessories
Net lamp weight

Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 63
LIT LN3 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg

Certificazioni



TRIMLESS



TRIM

