

ZIRKOL LINEAR CEILING UGR

Nuova lampada della collezione, Zirkol Linear UGR è dotata di un particolare gruppo ottico che consente un'illuminazione diretta con ridotto indice di abbagliamento ($UGR < 19$). Profilo in alluminio disponibile nelle finiture white e black e con temperatura colore LED di 3000K e 4000K. Zirkol Linear UGR è ora presentata nella versione Ceiling, completa di driver on-board ed è particolarmente adatta all'utilizzo in uffici e in ambienti di lavoro, dove è richiesto un elevato comfort visivo.



1,4M CEILING | 3000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	3000K
Luminous flux	3600lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42WBO
BZRLU414I42WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni



1,4M CEILING | 4000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	4000K
Luminous flux	3700lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42NBO
BZRLU414I42NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni

