



ILTI LUCE


ILTI LUCE




P23




P24




P04




P25




PROFILES AND LED STRIPS




P22



P13



P05



PROFILES AND LED STRIPS

IT

ILTI LUCE propone un'ampia selezione di profili lineari in alluminio adatti alla realizzazione di soluzioni luminose dedicate, capaci di rispondere alle più specifiche necessità di progetto. Completati di schermo di protezione e proposti in diverse dimensioni e con una gamma varia di LED strip compatibili. Alla fine della sezione, una guida presenta la migliore combinazione tra LED strip e profili lineari, indirizzando così l'utente verso la soluzione illuminotecnica più adeguata.

EN

ILTI LUCE offers a wide selection of aluminum linear profiles suitable for the realization of dedicated lighting solutions to meet the most specific project requirements. Supplied with protection shield and available in different sizes and with a varied range of compatible LED strips. At the end of the section, a guide presents the best combination of LED strips and linear profiles, directing the user towards the most suitable lighting solution.


DE

ILTI LUCE bietet eine umfangreiche Auswahl an Aluminiumprofilen, die sich ideal für die Umsetzung von maßgeschneiderten Beleuchtungslösungen eignen, um den spezifischsten Projektanforderungen gerecht zu werden. Die Profile werden mit Abdeckung geliefert und sind in verschiedenen Größen erhältlich, zudem stehen diverse kompatible LED-Streifen zur Verfügung. Am Ende des Abschnitts präsentiert ein Leitfaden die besten Kombinationen von LED-Streifen und linearen Profilen und leitet den Benutzer so zur geeignetsten Beleuchtungslösung.

FR


ILTI LUCE propose une large sélection de profilés linéaires en aluminium adaptés à la création de solutions d'éclairage dédiées, capables de répondre aux besoins des projets les plus spécifiques. Complet avec écran de protection et proposé en différentes tailles et avec une gamme variée de bandes LED compatibles. En fin de rubrique, un guide présente la meilleure combinaison entre rubans LED et profilés linéaires, orientant ainsi l'utilisateur vers la solution d'éclairage la plus adaptée.







P23

length	screen	finish	code
1m	opal	grey	BP23AAOP1M
2m	opal	grey	BP25AAOP2M
note	aluminum profile with opal screen included - black finish on demand		






BP23ENDCAPS
End caps




BP23CLIP
Clip

Accessories

version	profile	mounting	finish	code
End cap couple	P23	ceiling/wall	grey	BP23ENDCAPS
Clip P23	P23	wall	grey	BP23CLIP
note	Two fixing clip required per meter			




**Installation is recommended in wooden/plasterboard surfaces*




P24

length	screen	finish	code
1m	opal	grey	BP24AAOP1M
2m	opal	grey	BP25AAOP2M
3m	opal	grey	BP24AAOP3M
note	aluminum profile with opal screen included - black finish on demand		





BP24ENDCAPS
End caps




BP24CLIP
Fixing clip

Accessories

version	profile	mounting	finish	code
End caps couple	P24	ceiling/wall	grey	BP24ENDCAPS
Clip P24	P24	ceiling/wall	grey	BP24CLIP
note	Two fixing clip required per meter			




**Installation is recommended in wooden/plasterboard surfaces*




P04


length	screen	finish	code
1m	opal	grey	BP04AAOP1M
2m	opal	grey	BP04AAOP2M
3m	opal	grey	BP04AAOP3M
note aluminum profile with opal screen included - black finish on demand			




BP04ENDCAPS
End caps




BP04CORNERJ
Corner joint




BP04WALLB
Bracket




BP04CEILINGB
Ceiling/wall bracket




BP04RECCLIP
Recessed mounting bracket



BP04CLIP
Clip P04



BP04LINEARJ
Linear joint



BP04SUSPKIT
Suspension Kit


Accessories


version	profile	mounting	finish	code
End caps couple	P04	ceiling/wall	grey	BP04ENDCAPS
Corner joint	P04	all	grey	BP04CORNERJ
Linear joint	P04	all	grey	BP04LINEARJ
Bracket	P04	wall	grey	BP04WALLB
Ceiling/wall bracket	P04	ceiling/wall	grey	BP04CEILINGB
Recessed mounting bracket	P04	recessed	grey	BP04RECCLIP
Clip P04	P04	ceiling/wall	grey	BP04CLIP
Suspension Kit	P04	suspended	grey	BP04SUSPKIT
note Two fixing clip required per meter				




*It is possible a recessed installation only in wooden/plasterboard surfaces

ACCESSORIES PROFILES








P25




length	screen	finish	code
1m	opal	grey	BP25AAOP1M
2m	opal	grey	BP25AAOP2M
3m	opal	grey	BP25AAOP3M
note	aluminum profile with opal screen included -plastic profile for installation included- black finish on demand		



BP25ENDCAPS
End caps

Accessories

version	profile	mounting	finish	code
End caps couple	P25	ceiling/wall	grey	BP25ENDCAPS
note	Two fixing clip required per meter			




*A recessed installation is recommended in wooden surfaces



P22

length	screen	finish	code
1m	opal	grey	BP22AAOP1M
2m	opal	grey	BP22AAOP2M
3m	opal	grey	BP22AAOP3M
note	aluminum profile with opal screen included - black finish on demand		






BP22ENDCAPS
End caps


BP22CLIP
Fixing clip

Accessories

version	profile	mounting	finish	code
End caps couple	P22	ceiling/wall	grey	BP22ENDCAPS
Fixing clip	P22	ceiling/wall	grey	BP22CLIP
note	Two fixing clip required per meter			




*A recessed installation is recommended in wooden surfaces




P13

length	screen	finish	code
1m	opal	grey	BP13AAOP1M
2m	opal	grey	BP13AAOP2M
3m	opal	grey	BP13AAOP3M
note	aluminum profile with opal screen included - black finish on demand		





BP13ENDCAPS
End caps




BP13CLIP
Fixing clip

Accessories

version	profile	mounting	finish	code
End caps couple	P13	recessed	grey	BP13ENDCAPS
Fixing clip	P13	recessed	grey	BP13CLIP
note	Two fixing clip required per meter			




*A recessed installation is recommended in wooden/plasterboard surfaces




P05


length	screen	finish	code
1m	opal	grey	BP05AAOP1M
2m	opal	grey	BP05AAOP2M
3m	opal	grey	BP05AAOP3M
note aluminum profile with opal screen included - black finish on demand			



BSLACKITSTAF01
Plasterboard fixing clip






BP05CLIP-PLC
Wooden fixing clip



BP04LINEARJ
Linear joint

Accessories

version	ceiling thickness	profile	mounting	finish	code
Plasterboard fixing clip	min 0,3/max 4	P05	recessed	grey	BSLACKITSTAF01
Wooden fixing clip	min 3	P05	recessed	grey	BP05CLIP-PLC
Linear joint		P04	all	grey	BP04LINEARJ
note Two fixing clip required per meter					



*A recessed installation is recommended in wooden/plasterboard surfaces


N25

lumen/m
1200-1550lm

power/m
9,6W

Qty LED/m
128

dimensions
500x1x0,2




N19

lumen/m
1850-2000lm

power/m
14,5W

Qty LED/m
160

dimensions
600x0,5x0,2




N24

lumen/m
2064-2368lm

power/m
14,5W

Qty LED/m
160

dimensions
1000x1x0,2




N24HF





lumen/m
3400-4300lm

power/m
23W

Qty LED/m
160

dimensions
1000x1x0,2



N17 lumen/m 1590-1900lm power/m 15W Qty LED/m 240 dimensions 600x1x0,2 	N10 lumen/m 3090-3260lm power/m 19,2W Qty LED/m 112 dimensions 1000x1x0,2 	N21 lumen/m 570lm power/m 14,4W Qty LED/m 120 dimensions 500x1x0,  	N22 lumen/m 700lm power/m 15W Qty LED/m 192 dimensions 500x1,2x0,2  
--	---	---	--

N19

TECHNICAL INFORMATION

IP	IP20
Tension	24V
Power consumption	14,4W/m
Dimesnions	600x0,5x0,2
Qty LED/m	160
Sectionable every...	5
Luminous flux/m	>1850lm
CRI	90
Lifetime	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C
note	Warranty: 3 years


Color temperature

	2700K
	3000K
	4000K

Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-6022-0-00	LED strip 960 LED 86W IP20	90	2700K	14,4W	1800lm	
1-WKL-6023-0-00	LED strip 960 LED 86W IP20	90	3000K	14,4W	1850lm	
1-WKL-6024-0-00	LED strip 960 LED 86W IP20	90	4000K	14,4W	2000lm	
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles



P25

*to verify the compatibility of the profiles with various models of LED strips, please consult p.31
*do not connect more than 5m of strip, be careful of the voltage drop.

N24/N24HF

TECHNICAL INFORMATION

IP	IP20	IP20
Tension	24V	24V
Power consumption	14,5W/m	23W/m
Dimesnions	1000x1x0,2	1000x1x2
Qty LED/m	160	160
Sectionable every...	0,5	0,5
Luminous flux/m	>2064lm	>3400lm
CRI	90	>80
R9 index	>65 (CRI90)	
Lifetime	>L ₇₀ B ₅₀ >50000hrs	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C	-10 +35°C
note	Warranty: 3 years	Warranty: 3 years


Color temperature

	2200K
	2700K
	3000K
	3500K (on demand)
	4000K
	5000K (on demand)

Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-3020-1-00	LED strip 1600 LED 145W IP20	90	2700K	14,5W	2064lm	
1-WKL-3021-1-00	LED strip 1600 LED 145W IP20	90	3000K	14,5W	2224lm	
1-WKL-3022-1-00	LED strip 1600 LED 145W IP20	90	4000K	14,5W	2368lm	
1-WKL-3025-0-00	LED strip 1600 LED 230W IP20	>80	2700K	23W	3400lm	
1-WKL-3026-0-00	LED strip 1600 LED 230W IP20	>80	3000K	23W	3650lm	
1-WKL-3027-0-00	LED strip 1600 LED 230W IP20	>80	4000K	23W	4300lm	
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles




P23



P24



P04



P05



P22



P13

*to verify the compatibility of the profiles with various models of LED strips, please consult p.31

*do not connect more than 5m of strip, be careful of the voltage drop.

all dimensions are in cm

N17

TECHNICAL INFORMATION

IP	IP20
Tension	24V
Power consumption	15W/m
Dimesnions	600x0,5x0,2
Qty LED/m	240
Sectionable every...	3,3
Luminous flux/m	>1590lm
CRI	>95
R9 index	>83
Lifetime	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C
note	Warranty: 3 years


Color temperature

	2700K
	3000K
	4000K

Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-4500-0-00	LED strip 1440 LED 90W IP20	>97	2700K	15W	1590lm	
1-WKL-4501-0-00	LED strip 1440 LED 90W IP20	>97	3000K	15W	1770lm	
1-WKL-4502-0-00	LED strip 1440 LED 90W IP20	>97	4000K	15W	1905lm	
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles




P23



P24



P04



P05



P22



P13

*to verify the compatibility of the profiles with various models of LED strips, please consult p.31
*do not connect more than 5m of strip, be careful of the voltage drop.

N10

TECHNICAL INFORMATION

IP	IP20
Tension	24V
Power consumption	19,2W/m
Dimesnions	1000x1x0,2
Qty LED/m	112
Sectionable every...	7,14
Luminous flux/m	>3091lm
CRI	>80
Lifetime	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C
note	Warranty: 3 years


Color temperature

	3000K
	4000K

Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-3010-1-00	LED strip 1120 LED 192W IP20	>80	3000K	19,2W	3091lm	
1-WKL-3011-1-00	LED strip 1120 LED 192W IP20	>80	4000K	19,2W	3264lm	
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles



*to verify the compatibility of the profiles with various models of LED strips, please consult p.31
*do not connect more than 5m of strip, be careful of the voltage drop.

all dimensions are in cm

N21

TECHNICAL INFORMATION

IP	IP20
Tension	24V
Power consumption	14,4W/m
Dimesnions	500x1x0,2
Qty LED/m	120
Sectionable every...	5
Luminous flux/m	570lm
CRI	/
Lifetime	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C
note	Warranty: 3 years

Color temperature




RGB

Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-4510-0-00	RGB	/	/	14,4W	570lm	/
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles



*to verify the compatibility of the profiles with various models of LED strips, please consult p.31
*do not connect more than 5m of strip, be careful of the voltage drop.

all dimensions are in cm

N22

TECHNICAL INFORMATIONS

IP	IP20
Tension	24V
Power consumption	15W/m
Dimesnions	500x1,2x0,2
Qty LED/m	192
Sectionable every...	6,25
Luminous flux/m	700lm
CRI	90
Lifetime	>L ₇₀ B ₅₀ >50000hrs
Working temp.	-10 +35°C
note	Warranty: 3 years

Color temperature




2400K + RGB



Code	Description	CRI	CCT	power/m	lumen/m	energy eff. class
1-WKL-4511-0-00	RGB-white	90	2400K	15W	700lm	
note	3M VHB tape included					



DIMENSIONS



Compatible aluminum profiles




P23



P24



P04



P05



P22




P13

*to verify the compatibility of the profiles with various models of LED strips, please consult p.31
*do not connect more than 5m of strip, be careful of the voltage drop.

all dimensions are in cm

COMPATIBLE ALUMINUM PROFILES

							
	P23	P24	P04	P25	P22	P13	P05
 N25							
 N19							
 N24/HF							
 N17							
 N10							
 N21							
 N22							

-  LED Dot Free effect/ ideal for direct light solutions or continuous lines
-  Slightly visible LED Dot / ideal for indirect light solutions
-  Not compatible/ not recommended

ART DIRECTION AND GRAPHIC DESIGN
Guillaume Bloget and ILTI Luce

EDITION
April 2024

GENERAL INFORMATION

IT

Obiettivo di ILTI LUCE è quello di proporre soluzioni tecnologiche all'avanguardia, anche tramite un continuo e costante processo di aggiornamento. Per definizione la tecnologia è mutevole ed in costante evoluzione. Sugeriamo, per assicurare la consultazione delle informazioni più recenti sui prodotti, di verificare quelle disponibili sul nostro website www.iltiluce.com. Questo documento è stato redatto a Marzo 2024. Sostituisce ed aggiorna qualsiasi altra pubblicazione in relazione ai prodotti elencati.

A causa di naturali limiti tecnici di riproduzione e stampa, il colore dei modelli a catalogo è puramente indicativo e non può costituire motivo di rivalsa.

Ove non espressamente scritto, le lampadine non sono incluse nella vendita.

EN

ILTI LUCE's goal is to propose cutting-edge technological solutions, also through a constant updating process.

By definition, technology is changing and continuously evolving. To ensure the consultation of the latest product data, we recommend referring to the information available on our website www.iltiluce.com. This document was drafted in March 2024. It replaces and updates any other publication in relation to the listed products. Due to natural technical limitations of reproduction and printing, the colour of the models in the catalogue is purely indicative and cannot constitute grounds for recourse.

Unless expressly stated, light bulbs are not included in the sale.

DE

Das Ziel von ILTI LUCE ist die Entwicklung von technologischen Lösungen auf dem neuesten Stand, auch durch einen ständigen Aktualisierungsprozess. Die Technik entwickelt sich ständig weiter. Um die aktuellsten Produktunterlagen einzusehen, empfehlen wir, sich auf die Informationen auf unserer Website www.iltiluce.com zu beziehen. Dieses Dokument wurde im März 2024 verfasst. Es ersetzt und aktualisiert alle anderen Veröffentlichungen in Bezug auf die aufgeführten Produkte.

Aufgrund der technischen Grenzen der Reproduktion und des Drucks sind die Farben der im Katalog abgebildeten Modelle rein indikativ und können nicht als Reklamationsgrund dienen. Sofern nicht ausdrücklich angegeben, sind die Glühbirnen nicht im Verkauf enthalten.

FR

L'objectif de ILTI LUCE est de proposer des solutions technologiques

de pointe, également à travers un processus de mise à jour constante. Par définition, la technologie évolue et change continuellement. Pour garantir la consultation des dernières données produits, nous vous recommandons de vous référer aux informations disponibles sur notre site www.iltiluce.com.

Ce document a été établi en Mars 2024. Il remplace et met à jour toute autre publication relative aux produits cités.

En raison des limites techniques naturelles de reproduction et d'impression, la couleur des modèles du catalogue est purement indicative et ne peut constituer un motif de réclamation. Sauf mention expresse, les ampoules ne sont pas comprises dans la vente.

IT

L'elenco aggiornato dei prodotti con marchio UL ed ETL e le relative informazioni tecniche sono disponibili sul sito website: nemolighting.com/usa/

EN

The updated list of UL and ETL marked products and relevant technical information are available on the website: nemolighting.com/usa/

DE

Die aktualisierte Liste der UL- und ETL-zertifizierten Produkte und die entsprechenden technischen Informationen finden Sie auf der Website: nemolighting.com/usa/

FR

La liste actualisée des produits marqués UL et ETL et les informations techniques correspondantes sont disponibles sur le site web : nemolighting.com/usa/



Photometric data and more information available on our website:

www.iltiluce.com



Scan the code for Terms & Conditions

ILTI LUCE

ILTI LUCE

Strada Borgata Paradiso, 20
10036 Settimo Torinese - ITALY
Tel. +39 011 765 73 01
info@iltiluce.com

www.iltiluce.com

Part of

NEMO Group

NEMO SHOWROOM MONFORTE

Corso Monforte 19/A,
20122 Milan
Tel +39 02 970 703 40
monforte@nemolighting.com

NEMO GALERIE PARIS

44, Rue du Bac
75007 Paris
Tel +33 (0) 1 486 318 42
ruedubac@nemolighting.fr

NEMO USA

625 Jersey Avenue, Unit 7
New Brunswick, NJ 08901
Tel +1 800 734 5858
usa@nemolighting.com
nemolighting.com/usa/

NEMO COPENHAGEN

Store Kongensgade 118
1264 København
Denmark

