

ZIRKOL LINEAR CEILING UGR

Die neue Leuchte von dieser Kollektion Zirkol Linear UGR ist mit einer speziellen Einheit ausgestattet, die eine direkte Emission mit einem reduzierten Blendungsindex (UGR<19) ermöglicht. Das Aluminiumprofil ist in zwei Farben erhältlich: Schwarz und Weiß und mit zwei Farbtemperaturen: 3000K oder 4000K. Jetzt wird die Zirkol Linear UGR-Leuchte in der neuen Ceiling-Version mit eingebautem Treiber präsentiert. Es ist besonders geeignet für Büros Installationen und Arbeitsräumen, in denen hoher Sehkomfort erforderlich ist.



1,4M CEILING | 3000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	3000K
Luminous flux	3600lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42WBO
BZRLU414I42WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni



1,4M CEILING | 4000K

LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	4000K
Luminous flux	3700lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length white reflectors
Customization options	
Net lamp weight	1,75 kg

Codes

BZRLU414I42NBO
BZRLU414I42NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni

