

LIPARI

Family of recessed indoor downlights for accent lighting. The luminaire/fixture is rotatable by 30° vertically and 355° horizontally to allow the free orientation of the light in any direction.

The modular structure separates the lamp into several independent parts.

The outer rings with different finishes are simple to assemble and can be replaced easily to meet different opening requirements and appearance effects.

A variety of optical accessories are available to achieve different lighting effects.



RECESSED TRIMLESS 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m
Energy class	F
Accessories	Drivers, Lipari Lipari ring, Lipari ring
Net lamp weight	0,92 kg

Codes

LIP LW2 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW3 61

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m
Energy class	F
Accessories	Drivers, Lipari Lipari ring, Lipari ring
Net lamp weight	0,92 kg

Codes

LIP LW2 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
IP class	20
Dimensions	Ø12,2x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Drivers, Lipari | Lipari ring, Lipari ring
0,92 kg

Codes

LIP LW3 63

Structure

white

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,3 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 90
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 61
LIT LN2 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 15°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 15°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 61
LIT LN3 61

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 2700K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	2700K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW2 63
LIT LN2 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 3000K | 35°

LAMPING

Source	1x LED COB
Total power	22W
Emission	direct adjustable 35°
Switching	according to driver
Tension	600mA
Color temperature	3000K
Luminous flux	1400lm
Initial luminaire efficacy	64lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	ø13,8x15,5cm
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	driver and ring not included, orientable spot, anti light loss system, trimless recessed hole Ø 130mm, depth 200mm, trim recessed hole Ø 125mm, depth 200mm, cable length 0,4m

Energy class
Accessories
Net lamp weight

F
Lipari ring, Lipari ring
0,88 kg

Codes

LIT LW3 63
LIT LN3 63

Structure

white
black

PACKAGE



Package 01

Dimension: 46x46x36 cm / Gross weight: 1,25 kg

Certificazioni



TRIMLESS



TRIM

