

# PLINT BATTERY MINI

*Massimo Colagrande*

ILTI Luce's exploration of the world of architectural battery-powered lighting proceeds with an innovative design path that began with Plint. After reversing the accent lighting paradigm, ILTI Luce's miniaturization ability is revealed in its highly flexible reduced version. Inside a metal structure, a high-performance spot is powered by a highly flexible battery for accent lighting. Dimmer on board.



# 3000K

## LAMPING

Source	LED
Total power	2,4W
Emission	direct 14°
Switching	on board
Tension	5V
Color temperature	3000K
Luminous flux	185lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	20
Dimensions	13x11,6
Ambient temperature range	+5°C / +35°C
Performance ambient temperature	25°C
Notes	cable included (USB-C), rechargeable, 5 hours battery life, 4,5 hours charge time (light off)
Energy class	G
Net lamp weight	0,55 kg

## Codes

PLM BNN 11  
PLM BWN 11  
PLM BON 11  
PLM BDN 11

## Structure

black  
white  
gold  
silver

## PACKAGE

Package 01      Dimension: 19x19x8 cm / Gross weight: 0,70 kg

## Certificazioni

