

WALKLINE WALL WASHER

WALKLINE is a walkable, linear LED 24V DC system for outdoor signalization or wall washer lighting. The WALKLINE consists of a naturally anodised aluminium profile with an opal resin coating for homogeneous light emission or with a wall washer optic. Available in various standard lengths. Dimmable 1-10V, DALI or DMX. Recessed box installation included. WALKLINE and WALKLINE WALL WASHER are extremely resistant against scratches, foot and drive traffic and lend themselves for outdoor settings where signalling or decorative lighting is required.



0,61M | 3000K

LAMPING

Source	LED strip
Total power	12W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1030lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	61x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options	body length
Accessories	Drivers 24VDC + DALI interface,
Net lamp weight	1,75 kg

Codes

BWLK0206W52WAA

Structure


grey

PACKAGE

Package 01

Dimension: 52x3x9 cm / Gross weight: 1,75 kg

Certificazioni



0,61M | 4000K

LAMPING

Source	LED strip
Total power	12W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1144lm
Initial luminaire efficacy	95lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	61x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options	body length
Accessories	Drivers 24VDC + DALI interface,
Net lamp weight	1,75 kg

Codes

BWLK0206W52NAA

Structure


grey

PACKAGE

Package 01

Dimension: 52x3x9 cm / Gross weight: 1,75 kg

Certificazioni



1,21M | 3000K

LAMPING

Source	LED strip
Total power	24W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	2060lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	121x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options
Accessories
Net lamp weight

body length
Drivers 24VDC + DALI interface,
3,5 kg

Codes

BWLK0209W52WAA

Structure


grey

PACKAGE

Package 01

Dimension: 103x3x9 cm / Gross weight: 3,5 kg

Certificazioni



1,21M | 4000K

LAMPING

Source	LED strip
Total power	24W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	2288lm
Initial luminaire efficacy	95lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	121x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options
Accessories
Net lamp weight

body length
Drivers 24VDC + DALI interface,
3,5 kg

Codes

BWLK0209W52NAA

Structure


grey

PACKAGE

Package 01

Dimension: 103x3x9 cm / Gross weight: 3,5 kg

Certificazioni



1,96M | 3000K

LAMPING

Source LED strip
Total power 40W
Emission asymmetric 45°
Switching according to driver
Tension 24VDC
Color temperature 3000K
Luminous flux 3433lm
Initial luminaire efficacy 86lm/W
Initial chromaticity SDCM<3
Typ CRI 90
IP class 67
Dimensions 196x3x9,25cm
Materials aluminium
Ambient temperature range -20°C / +35°C
Performance ambient temperature 25°C
Mechanical impact protection code IK10
Notes

Customization options
Accessories
Net lamp weight

driver not included, cable length 1m, certified
500kg static load, 3500kg dynamic load
body length
Drivers 24VDC + DALI interface,
7 kg

Codes

BWLK0220W52WAA

Structure


grey

PACKAGE

Package 01

Dimension: 200x3x9 cm / Gross weight: 7 kg

Certificazioni



1,96M | 4000K

LAMPING

Source
Total power
Emission
Switching
Tension
Color temperature
Luminous flux
Initial luminaire efficacy
Initial chromaticity
Typ CRI
IP class
Dimensions
Materials
Ambient temperature range
Performance ambient temperature
Mechanical impact protection code
Notes

Customization options
Accessories
Net lamp weight

LED strip
40W
asymmetric 45°
according to driver
24VDC
4000K
3815lm
95lm/W
SDCM<3
90
67
196x3x9,25cm
aluminium
-20°C / +35°C
25°C
IK10

driver not included, cable length 1m, certified
500kg static load, 3500kg dynamic load
body length
Drivers 24VDC + DALI interface,
7 kg

Codes

BWLK0220W52NAA

Structure

grey

PACKAGE

Package 01

Dimension: 200x3x9 cm / Gross weight: 7 kg

Certificazioni

