

ZIRKOL ACOUSTIC

The ZIRKOL family represents the optimal balance between design and lighting, making it essential in the world of architecture. ZIRKOL ACOUSTIC, a pendant lamp that combines lighting and acoustics. Designed to provide a comfortable atmosphere, it features a sound-absorbing circular panel covered with a recycled polyester fabric in a grey colour.



1M | DOWNLIGHT - 2700K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	45W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	2700K
Luminous flux	2616lm
Initial luminaire efficacy	58lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium + polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1610G15DBG
BZAC1610G15DNG

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni



1M | DOWNLIGHT - 3000K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	45W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	3000K
Luminous flux	2769lm
Initial luminaire efficacy	62lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium + polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1610G15WBG
BZAC1610G15WNG

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni



1M | DOWNLIGHT - 4000K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	45W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	4000K
Luminous flux	3077lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium + polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1610G15NBG
BZAC1610G15NNG

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni



1M | UP-DOWNLIGHT - 2700K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	90W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	2700K
Luminous flux	5231lm
Initial luminaire efficacy	52lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium + polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1710G15DBG
BZAC1710G15DNG

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni



1M | UP-DOWNLIGHT - 3000K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	90W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	3000K
Luminous flux	5539lm
Initial luminaire efficacy	62lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium+polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1710G15WBG
BZAC1710G15WNG

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni



1M | UP-DOWNLIGHT - 4000K

ZIRKOL ACOUSTIC

LAMPING

Source	LED strip
Total power	90W
Emission	diffused orientable
Switching	DALI
Tension	24V
Color temperature	4000K
Luminous flux	6154lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium+polyester
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	round canopy with 1 x driver 75W (110/24V) 1 x dimmer DALI 1 x electrical cable 4m 3 x adjustable metal cable (length from 3m to 0,5m) ceiling attachment included Grey sound-absorbing panel 100% polyester FR blue navy or deep green panels available on demand RAL 9005 black RAL 9016 white shipped assembled blue navy or deep green panels

Customization options
Net lamp weight

5,83 kg

Codes

BZAC1710G15NBG
BZAC1710G15NNG

Structure

white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 8,61 kg

Certificazioni

