

ZIRKOL LINEAR CEILING UGR

New lamp of the collection, Zirkol Linear UGR is equipped with a particular optical unit that allows direct emission with a reduced glare index (UGR <19). Aluminium structure available in black or white finish and two LED colour temperatures: 3000K or 4000K. Now Zirkol Linear UGR lamp is presented in the new Ceiling version with driver on-board. It is particularly suitable for installation in offices and work environments where high visual comfort is required.



1,4M CEILING | 3000K



LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	3000K
Luminous flux	3600lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white
Customization options	length white reflectors
Net lamp weight	1,75 kg

Codes

BZRLU414I42WBO
BZRLU414I42WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni



1,4M CEILING | 4000K



LAMPING

Source	LED strip
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	24V
Color temperature	4000K
Luminous flux	3700lm
Initial luminaire efficacy	90lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	146x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white
Customization options	length white reflectors
Net lamp weight	1,75 kg

Codes

BZRLU414I42NBO
BZRLU414I42NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 204x11x11 cm / Gross weight: 3,55 kg

Certificazioni

