

ZIRKOL TRACK UGR

New addition to the collection, Zirkol Linear Track UGR features a special optical unit that allows direct emission with a reduced glare index ($UGR < 19$). Suitable for installation in offices and workplaces where high visual comfort is required. Aluminium structure available in the finishes white and black and with LED colour temperatures of 3000K and 4000K. Zirkol Linear Track UGR is compatible with 3C/0-10V tracks. Driver on board.



0,84M | 3000M

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2160lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	



Codes

BZRL54084I42NBO
BZRL54084I42NNE

Structure

white
black

Certificazioni



1,15M | 3000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2957lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54115I42NBO
BZRL54115I42NNE

Structure

white
black

Certificazioni



0,84M | 4000K

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2220lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54084I42WBO
BZRL54084I42WNE

Structure

white
black

Certificazioni



1,15M | 4000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	3039lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5,10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	

Codes

BZRL54115I42WBO
BZRL54115I42WNE

Structure

white
black

Certificazioni

