

MINIFLUX LINEA TRANSPARENT

Miniflux Linea Transparent est un système à LED en suspension pour l'éclairage intérieur. Corps en profilé aluminium sur lequel est positionnée une bande de ruban LED 24V DC. CRI>97. Diffuseur en polycarbonate transparent. Disponible en finition noire, blanche et or. Miniflux est disponible en deux températures de couleur et dans les versions TRIAC et DALI. Driver déporté inclus.



TRIAC | 2700K

LAMPING

Source	LED strip
Total power	15W
Emission	direct
Switching	TRIAC
Tension	24V
Color temperature	2700K
Luminous flux	852lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	>97
IP class	40
Dimensions	106xø2cm
Materials	polycarbonate
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	

Customization options

Energy class	F
Net lamp weight	0,6 kg

Codes

BMLT2710G26DAN
BMLT2710G26DBO
BMLT2710G26DAO

Structure


black
white
gold

PACKAGE

Package 01

Dimension: 140x8x8 cm / Gross weight: 2,4 kg

Certificazioni



TRIAC | 3000K

LAMPING

Source	LED strip
Total power	15W
Emission	direct
Switching	TRIAC
Tension	24V
Color temperature	3000K
Luminous flux	897lm
Initial luminaire efficacy	60m/W
Initial chromaticity	SDCM<3
Typ CRI	>97
IP class	40
Dimensions	106xø2cm
Materials	polycarbonate
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	

Customization options
Energy class
Net lamp weight

included: canopy with 1 x driver | 1 x electrical
cable 3m | 2 x adjustable metal cables 2m | driver
included | canopy RAL 9005 black for black finish |
canopy RAL 9016 white for white/gold finish
tube length
F
0,6 kg

Codes

BMLT2710G26WAN
BMLT2710G26WBO
BMLT2710G26WAO

Structure


black
white
gold

PACKAGE

Package 01

Dimension: 140x8x8 cm / Gross weight: 2,4 kg

Certificazioni



DALI | 2700K

LAMPING

Source	Linear LED
Total power	15W
Emission	direct
Switching	DALI
Tension	24V
Color temperature	2700K
Luminous flux	852lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	>97
IP class	40
Dimensions	106xø2cm
Materials	polycarbonate
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	

Customization options
Energy class
Net lamp weight

included: canopy with 1 x driver | 1 x electrical
cable 3m | 2 x adjustable metal cables 2m | driver
included | canopy RAL 9005 black for black finish |
canopy RAL 9016 white for white/gold finish
tube length
F
0,6 kg

Codes

BMLT1610G26DAN
BMLT1610G26DBO
BMLT1610G26DAO

Structure


black
white
gold

PACKAGE

Package 01

Dimension: 140x8x8 cm / Gross weight: 2,4 kg

Certificazioni



DALI | 3000K

LAMPING

Source	LED strip
Total power	15W
Emission	direct
Switching	DALI
Tension	24V
Color temperature	3000K
Luminous flux	897lm
Initial luminaire efficacy	60m/W
Initial chromaticity	SDCM<3
Typ CRI	>97
IP class	40
Dimensions	106xø2cm
Materials	polycarbonate
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	included: canopy with 1 x driver 1 x electrical cable 3m 2 x adjustable metal cables 2m driver included canopy RAL 9005 black for black finish canopy RAL 9016 white for white/gold finish
Customization options	tube length
Energy class	F
Net lamp weight	0,6 kg

Codes

BMLT1610G26WAN
BMLT1610G26WBO
BMLT1610G26WAO

PACKAGE

Package 01

Structure

black
white
gold

Dimension: 140x8x8 cm / Gross weight: 2,4 kg

Certificazioni

