

# ZIRKOL LINEAR WALL

Dédié à l'éclairage indirect et à forte connotation décorative, Zirkol Linear Wall est la nouvelle lampe de la collection, proposée avec une forme linéaire et une fixation murale. Trois températures de couleur LED disponibles, 2700K, 3000K ou 4000K et finitions noire, blanc et l'or.



1M | 2700K

ZIRKOL LINEAR WALL

### LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 14,5W                                                                                                                           |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 2700K                                                                                                                           |
| Luminous flux                   | 833lm                                                                                                                           |
| Initial luminaire efficacy      | 57lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 100x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 1,32 kg                                                                                                                         |

### Codes

BZRL4010G15DBO  
BZRL4010G15DNE  
BZRL4010G15DOR


### Structure

white  
black  
gold

### PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

### Certificazioni



1M | 3000K

ZIRKOL LINEAR WALL

### LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 14,5W                                                                                                                           |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 3000K                                                                                                                           |
| Luminous flux                   | 882lm                                                                                                                           |
| Initial luminaire efficacy      | 61lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 100x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 1,32 kg                                                                                                                         |

### Codes

BZRL4010G15WBO  
BZRL4010G15WNE  
BZRL4010G15WOR

### Structure

white  
black  
gold

### PACKAGE

Package 01      Dimension: 115x11x11 cm / Gross weight: 2,12 kg

### Certificazioni



1M | 4000K

ZIRKOL LINEAR WALL

### LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 14,5W                                                                                                                           |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 4000K                                                                                                                           |
| Luminous flux                   | 980lm                                                                                                                           |
| Initial luminaire efficacy      | 68lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 100x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 1,32 kg                                                                                                                         |

### Codes

BZRL4010G15NBO  
BZRL4010G15NNE  
BZRL4010G15NOR

### Structure

white  
black  
gold

### PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

### Certificazioni



2M | 2700K

LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 29W                                                                                                                             |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 2700K                                                                                                                           |
| Luminous flux                   | 1666lm                                                                                                                          |
| Initial luminaire efficacy      | 57lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 200x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 2,69 kg                                                                                                                         |

Codes

BZRL4020G15DBO  
BZRL4020G15DNE  
BZRL4020G15DOR


Structure

white  
black  
gold

PACKAGE

Package 01      Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



ZIRKOL LINEAR WALL



LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 29W                                                                                                                             |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 3000K                                                                                                                           |
| Luminous flux                   | 1764lm                                                                                                                          |
| Initial luminaire efficacy      | 61lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 200x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 2,69 kg                                                                                                                         |

Codes

BZRL4020G15WBO  
BZRL4020G15WNE  
BZRL4020G15WOR

Structure

white  
black  
gold

PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 250x11x11 cm / Gross weight: 4,69 kg |
|------------|-------------------------------------------------|

Certificazioni



LAMPING

|                                 |                                                                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Source                          | LED strip                                                                                                                       |
| Total power                     | 29W                                                                                                                             |
| Emission                        | diffused                                                                                                                        |
| Switching                       | ON/OFF                                                                                                                          |
| Tension                         | 220/240V                                                                                                                        |
| Color temperature               | 4000K                                                                                                                           |
| Luminous flux                   | 1960lm                                                                                                                          |
| Initial luminaire efficacy      | 68lm/W                                                                                                                          |
| Initial chromaticity            | SDCM<3                                                                                                                          |
| Typ CRI                         | 90                                                                                                                              |
| IP class                        | 40                                                                                                                              |
| Dimensions                      | 200x2,6x5cm                                                                                                                     |
| Materials                       | aluminium                                                                                                                       |
| Ambient temperature range       | 0°C / +35°C                                                                                                                     |
| Performance ambient temperature | 25°C                                                                                                                            |
| Notes                           | included: 1 x driver Ultraslim 60W (220/240V)  <br>integrated driver   RAL 9005 black   RAL 9016 white<br>length   lumen output |
| Customization options           |                                                                                                                                 |
| Net lamp weight                 | 2,69 kg                                                                                                                         |

Codes

BZRL4020G15NBO  
BZRL4020G15NNE  
BZRL4020G15NOR

Structure

white  
black  
gold

PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 250x11x11 cm / Gross weight: 4,69 kg |
|------------|-------------------------------------------------|

Certificazioni

