ZIRKOL SPOT

ZIRKOL contient l’équilibre parfait entre design et éclairage, une combinaison qui la rend indispensable dans le monde de l’architecture. Chaque produit est disponible en différentes finitions et tailles. Toutes les formes ZIRKOL sont réalisées avec le même profilé pour allier design et esthétique. Disponible en simple émission downlight et LED spot.

1M | 2700K - DALI

LAMPING

Source	strip LED + spot
Total power	60W
Emission	direct downlight
Switching	DALI
Tension	110/240V
Color temperature	2700K
Luminous flux	3955lm
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium
Notes	included: round canopy with 1 driver 75W (110/240V) | 1x dimmer DALI | 1 electrical cable 4m | 3x adjustable spots up to 90° | 3x adjustable metal cables (length from 3m to 0,5m) ceiling attachment included | RAL 9005 black | RAL 9016 white | 396lm for single spot | Shipped assembled



Codes	*Structure*
BZRCF610G15DBO	white
BZRCF610G15DNE	black
BZRCF610G15DOR	gold

Certificazioni

1M | 3000K - DALI

LAMPING

Source	strip LED + spot
Total power	60W
Emission	direct downlight
Switching	DALI
Tension	110/240V
Color temperature	3000K
Luminous flux	4393lm
Typ CRI	90
IP class	40
Dimensions	ø100x5cm
Materials	aluminium
Notes	included: round canopy with 1 driver 75W (110/240V) | 1x dimmer DALI | 1 electrical cable 4m | 3x adjustable spots up to 90° | 3x adjustable metal cables (length from 3m to 0,5m) ceiling attachment included | RAL 9005 black | RAL 9016 white | 396lm for single spot | Shipped assembled

Codes	*Structure*
BZRCF610G15WBO	white
BZRCF610G15WNE	black
BZRCF610G15WOR	gold

Certificazioni



1,5M | 2700K - DALI

LAMPING

Source	strip LED + spot
Total power	93W
Emission	direct downlight
Switching	DALI
Tension	110/240V
Color temperature	2700K
Luminous flux	5515lm
Typ CRI	90
IP class	40
Dimensions	ø150x5cm
Materials	aluminium
Notes	included: round canopy with 1 driver 100W (110/240V) | 1x dimmer DALI | 1 electrical cable 4m | 5x adjustable spots up to 90° | 3x adjustable metal cables (length from 3m to 0,5m) ceiling attachment included | RAL 9005 black | RAL 9016 white | 396lm for single spot | Shipped assembled

Codes	*Structure*
BZRCF615G15DBO	white
BZRCF615G15DNE	black
BZRCF615G15DOR	gold

Certificazioni



1,5M | 3000K - DALI

LAMPING

Source	strip LED + spot
Total power	93W
Emission	direct downlight
Switching	DALI
Tension	110/240V
Color temperature	3000K
Luminous flux	6130lm
Typ CRI	90
IP class	40
Dimensions	ø150x5cm
Materials	aluminium
Notes	included: round canopy with 1 driver 100W (110/240V) | 1x dimmer DALI | 1 electrical cable 4m | 5x adjustable spots up to 90° | 3x adjustable metal cables (length from 3m to 0,5m) ceiling attachment included | RAL 9005 black | RAL 9016 white | 396lm for single spot | Shipped assembled

Codes	*Structure*
BZRCF615G15WBO	white
BZRCF615G15WNE	black
BZRCF615G15WOR	gold

Certificazioni