

FLEX CEILING

FLEX è una famiglia di spots orientabili miniaturizzati dedicati all'illuminazione d'accento.

A seconda dell'ambiente e delle necessità di illuminazione, FLEX propone spots con fissaggio, ottiche e finiture differenti. La collezione FLEX è composta da FLEX CEILING, la gamma con ottica fissa e zoom 15°- 45°, disponibile nelle finiture nero, oro, grigio anodizzato naturale e grigio bronzo. Lo snodo, presente in entrambe le versioni, consente di fissare gli spots a plafone o a binario e di orientarli a piacere, secondo le necessità di illuminazione, senza che ci siano cavi visibili all'esterno.



FIXED OPTIC | 3000K - 20°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 20°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21WAN
BFLE0401F21WAO
BFLE0401F21WAA
BFLE0401F21WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 3000K - 30°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 30°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°
Notes	driver not included, orientable spot $\pm 42^\circ$, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421WAN
BFLE0401421WAO
BFLE0401421WAA
BFLE0401421WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 20°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 20°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21NAN
BFLE0401F21NAO
BFLE0401F21NAA
BFLE0401F21NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 30°

LAMPING

Source	LED
Total power	4,2W
Emission	direct 30°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x8cm
Materials	anodized aluminum
Ambient temperature range	-20°C / +25°C
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421NAN
BFLE0401421NAO
BFLE0401421NAA
BFLE0401421NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 3000K

LAMPING

Source	LED
Total power	4,2W
Emission	direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	76lm (45°)
Initial luminaire efficacy	18lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x10,7cm
Materials	anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401921WAN

Structure

black

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 4000K

LAMPING

Source	LED
Total power	4,2W
Emission	direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	80lm (45°)
Initial luminaire efficacy	19lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
IP class	40
Dimensions	ø3,3x10,7cm
Materials	anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	25°C
Notes	driver not included, orientable spot ±42°, orientable spot on ball joint 360°, series connection
Customization options	CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,10 kg

Codes

BFLE0401921NAN

Structure

black

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,14 kg

Certificazioni



FIXED OPTIC



ZOOM OPTIC

