

WALKLINE WALL WASHER

WALKLINE è un sistema lineare di illuminazione a LED 24V DC per esterni.

È proposto in due versioni dedicate rispettivamente ad un'illuminazione omogenea, ottenuta tramite una superficie in resina opale o wall-washer, dotato di apposita ottica. La famiglia WALKLINE viene proposta in differenti lunghezze e temperature colore. È dimmerabile 1-10V, DALI o DMX ed il fissaggio avviene tramite cassaforma a pavimento inclusa. WALKLINE e WALKLINE WALL-WASHER hanno un elevato indice di resistenza: sono infatti entrambi calpestabili e carrabili. Trovano applicazione in ambientazioni outdoor con necessità di illuminazione di segnalazione o decorativa.



0,61M | 3000K

LAMPING

Source	LED strip
Total power	12W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	1030lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	61x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options
Accessories
Net lamp weight

body length
Drivers 24VDC + DALI interface,
1,75 kg

Codes

BWLK0206W52WAA

Structure


grey

PACKAGE

Package 01

Dimension: 52x3x9 cm / Gross weight: 1,75 kg

Certificazioni



0,61M | 4000K

LAMPING

Source	LED strip
Total power	12W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	1144lm
Initial luminaire efficacy	95lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	61x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options
Accessories
Net lamp weight

body length
Drivers 24VDC + DALI interface,
1,75 kg

Codes

BWLK0206W52NAA

Structure


grey

PACKAGE

Package 01

Dimension: 52x3x9 cm / Gross weight: 1,75 kg

Certificazioni



1,21M | 3000K

LAMPING

Source	LED strip
Total power	24W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	2060lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	121x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load

Customization options
Accessories
Net lamp weight

body length
Drivers 24VDC + DALI interface,
3,5 kg

Codes

BWLK0209W52WAA

Structure


grey

PACKAGE

Package 01

Dimension: 103x3x9 cm / Gross weight: 3,5 kg

Certificazioni



1,21M | 4000K

LAMPING

Source	LED strip
Total power	24W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	4000K
Luminous flux	2288lm
Initial luminaire efficacy	95lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	121x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load body length
Customization options	
Accessories	Drivers 24VDC + DALI interface,
Net lamp weight	3,5 kg

Codes

BWLK0209W52NAA

PACKAGE

Package 01

Certificazioni




LED strip
24W
asymmetric 45°
according to driver
24VDC
4000K
2288lm
95lm/W
SDCM<3
90
67
121x3x9,25cm
aluminium
-20°C / +35°C
25°C
IK10
driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load body length
Drivers 24VDC + DALI interface,
3,5 kg

Structure

grey

Dimension: 103x3x9 cm / Gross weight: 3,5 kg



1,96M | 3000K

LAMPING

Source	LED strip
Total power	40W
Emission	asymmetric 45°
Switching	according to driver
Tension	24VDC
Color temperature	3000K
Luminous flux	3433lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	196x3x9,25cm
Materials	aluminium
Ambient temperature range	-20°C / +35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	driver not included, cable length 1m, certified 500kg static load, 3500kg dynamic load body length

Customization options
Accessories
Net lamp weight

Structure


grey

PACKAGE

Package 01

Dimension: 200x3x9 cm / Gross weight: 7 kg

Certificazioni



1,96M | 4000K

LAMPING

Source
Total power
Emission
Switching
Tension
Color temperature
Luminous flux
Initial luminaire efficacy
Initial chromaticity
Typ CRI
IP class
Dimensions
Materials
Ambient temperature range
Performance ambient temperature
Mechanical impact protection code
Notes

Customization options
Accessories
Net lamp weight

LED strip
40W
asymmetric 45°
according to driver
24VDC
4000K
3815lm
95lm/W
SDCM<3
90
67
196x3x9,25cm
aluminium
-20°C / +35°C
25°C
IK10

driver not included, cable length 1m, certified
500kg static load, 3500kg dynamic load
body length
Drivers 24VDC + DALI interface,
7 kg

Codes

BWLK0220W52NAA

Structure

grey

PACKAGE

Package 01

Dimension: 200x3x9 cm / Gross weight: 7 kg

Certificazioni

