

ZIRKOL CIRCLE PLUS

ZIRKOL – C Plus è una famiglia di lampade circolari a sospensione ideale per l'illuminazione generale e decorativa di ambienti.

Corpo in alluminio anodizzato e schermo di protezione opale per un'illuminazione omogenea. CRI > 80.

L'emissione di luce può essere diretta o bi-emissione con alto flusso luminoso e con tre differenti temperature colore.



Ø 1M - DOWNLIGHT - 3000K | ON-OFF

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	4000lm
Initial luminaire efficacy	36lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC0310G24WBO
PZRC0310G24WNE

Structure


white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K | DALI

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	4000lm
Initial luminaire efficacy	36lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1610G24WBO
PZRC1610G24WNE


Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K | ON-OFF

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	2000lm + 4000lm
Initial luminaire efficacy	40lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1410G24WBO
PZRC1410G24WNE


Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K | DALI

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	2000lm + 4000lm
Initial luminaire efficacy	40lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1710G24WBO
PZRC1710G24WNE


Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	7500lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC0310G15WBO
PZRC0310G15WNE


Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7500lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1610G15WBO
PZRC1610G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	4000lm + 7500lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1410G15WBO
PZRC1410G15WNE

Structure

white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	4000lm + 7500lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1710G15WBO
PZRC1710G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K | ON-OFF

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	5200lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC0315G24WBO
PZRC0315G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K | DALI

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	5200lm
Initial luminaire efficacy	37lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi; shapes, sizes, CCT, RGB, RGBW
Customization options	
Net lamp weight	5,4 kg

Codes

PZRC1615G24WBO
PZRC1615G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K | ON-OFF

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	2500lm + 5200lm
Initial luminaire efficacy	38lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC1415G24WBO
PZRC1415G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K | DALI

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	2500lm + 5200lm
Initial luminaire efficacy	38lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC1715G24WBO
PZRC1715G24WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	9800lm
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC0315G15WBO
PZRC0315G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	9800lm
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,5 kg

Codes

PZRC1615G15WBO
PZRC1615G15WNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	3000K
Luminous flux	5200lm + 9800lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC1415G15WBO
PZRC1415G15WNE

Structure

white
black

PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 3000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	5200lm + 9800lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	

Customization options

Net lamp weight

remote driver and DALI interface included;
suspension kit included; cable 5m; optional
controls: DMX, Casambi
shapes, sizes, CCT, RGB, RGBW
5,9 kg

Codes

PZRC1715G15WBO

PZRC1715G15WNE

Structure

white

black

PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	4000K
Luminous flux	7500lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver ncluded; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC0310G15NBO
PZRC0310G15NNE

Structure

white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	110W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	7500lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1610G15NBO
PZRC1610G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



Ø100/150

Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	4000K
Luminous flux	4000lm + 7500lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	4 kg

Codes

PZRC1410G15NBO
PZRC1410G15NNE

Structure

white
black

PACKAGE

Package 01

Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	150W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	4000lm + 7500lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi shapes, sizes, CCT, RGB, RGBW
Customization options	
Net lamp weight	4 kg

Codes

PZRC1710G15NBO
PZRC1710G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 115x115x12 cm / Gross weight: 6,5 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	4000K
Luminous flux	9800lm
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	Ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC0315G15NBO
PZRC0315G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	140W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	9800lm
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC1615G15NBO
PZRC1615G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | ON-OFF

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	ON/OFF
Tension	24VDC
Color temperature	4000K
Luminous flux	5200lm + 9800lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	remote driver interface included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	shapes, sizes, CCT, RGB, RGBW
Net lamp weight	5,4 kg

Codes

PZRC1415G15NBO
PZRC1415G15NNE

Structure

white
black

PACKAGE

Package 01 Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |

Ø 1,5M - UP-DOWNLIGHT - 4000K - HIGH FLUX | DALI

LAMPING

Source	LED strip
Total power	200W
Emission	diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	5200lm + 9800lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	> 80
IP class	40
Dimensions	ø150x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	

Customization options

Net lamp weight

remote driver and DALI interface included;
suspension kit included; cable 5m; optional
controls: DMX, Casambi
shapes, sizes, CCT, RGB, RGBW
5,4 kg

Codes

PZRC1715G15NBO

PZRC1715G15NNE

Structure

white

black

PACKAGE

Package 01

Dimension: 165x165x12 cm / Gross weight: 8,9 kg

Certificazioni



| Ø100/150 |