

ZIRKOL LINEAR CEILING

Zirkol Linear Ceiling si concretizza con profilo lineare in alluminio proposto nelle finiture black, white e matte gold. È completo di schermo opale per un'illuminazione diretta e omogenea, con temperatura colore LED di 2700K, 3000K o 4000K. Driver on-board.



1M CEILING | 2700K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	1900lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5
Materials	aluminum
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Energy class	E
Net lamp weight	1,32 kg

Codes

BZRLU410G15DBO
BZRLU410G15DNE
BZRLU410G15DOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M CEILING | 3000K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2000lm
Initial luminaire efficacy	71lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5
Materials	aluminum
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Energy class	E
Net lamp weight	1,32 kg

Codes

BZRLU410G15WBO
BZRLU410G15WNE
BZRLU410G15WOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M CEILING | 4000K



LAMPING

Source	LED strip
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2100lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white
Customization options	length lumen output
Energy class	D
Net lamp weight	1,32 kg

Codes

BZRLU410G15NBO
BZRLU410G15NNE
BZRLU410G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



2M CEILING | 2700K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	3800lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Energy class	E
Net lamp weight	2,69 kg

Codes

BZRLU420G15DBO
BZRLU420G15DNE
BZRLU420G15DOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



2M CEILING | 3000K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	4000lm
Initial luminaire efficacy	71lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Energy class	E
Net lamp weight	2,69 kg

Codes

BZRLU420G15WBO
BZRLU420G15WNE
BZRLU420G15WOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



2M CEILING | 4000K



LAMPING

Source	LED strip
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	4200lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Energy class	D
Net lamp weight	2,69 kg

Codes

BZRLU420G15NBO
BZRLU420G15NNE
BZRLU420G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni

