

ZIRKOL SQUARE PLUS

ZIRKOL S Plus è una famiglia di lampade di forma quadrata a sospensione ideale per l'illuminazione generale e decorativa di ambienti.

Corpo in alluminio anodizzato e schermo di protezione opale per un'illuminazione omogenea. CRI > 80.

L'emissione di luce può essere diretta o bi-emissione con alto flusso luminoso e con differenti temperature colore.



1X1M | DOWNLIGHT - 3000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS0310G15WNE


Structure

black

PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	75W
Emission	Diffusion orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1610G15WNE

Structure


black

PACKAGE

Package 01

Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | UP - DOWNLIGHT - 3000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1410G15WNE


Structure

black

PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1710G15WNE

Structure


black

PACKAGE

Package 01

Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | DOWNLIGHT - 4000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	75W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS0310G15NNE


Structure

black

PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	75W
Emission	Diffusion orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1610G15NNE

Structure


black

PACKAGE

Package 01

Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | UP - DOWNLIGHT - 4000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	80lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1410G15NNE


Structure

black

PACKAGE

Package 01 Dimension: 105x105x5 cm / Gross weight: 9,12 kg

Certificazioni



1X1M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	150W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	4800lm + 7600lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	100x100x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	5,7 kg

Codes

PZRS1710G15NNE

Structure


black

PACKAGE

Package 01

Dimension: 105x105x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | DOWNLIGHT - 3000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS0315G15WNE


Structure

black

PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS1615G15WNE

Structure


black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | UP - DOWNLIGHT - 3000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS1415G15WNE

Structure


black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS1715G15WNE

Structure


black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | DOWNLIGHT - 4000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	11000lm
Initial luminaire efficacy	100lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver included; suspension kit included; cable 5m; optional controls: DALI, DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS0315G15NNE


Structure

black

PACKAGE

Package 01 Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	112,5W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	11000lm
Initial luminaire efficacy	82lm/W
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	0°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes
Net lamp weight	8,56 kg

Codes

PZRS1615G15NNE

Structure


black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | UP - DOWNLIGHT - 4000K - HIGH FLUX

LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	82lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	20°C / 35°
Performance ambient temperature	25°
Notes	

Customization options

Net lamp weight

remote driver included; suspension kit included;
cable 5m; optional controls: DALI, DMX, Casambi
Shapes, sizes, colour temperatures, RGB, RGBW
8,56 kg

Codes

PZRS1415G15NNE

Structure


black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 12,06 kg

Certificazioni



1,5X1,5M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

LAMPING

Source	Linear LED
Total power	225W
Emission	Diffused orientable
Switching	DALI
Tension	24VDC
Color temperature	4000K
Luminous flux	7200lm + 11000lm
Initial luminaire efficacy	100lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
IP class	40
Dimensions	150x150x5cm
Materials	Aluminium
Ambient temperature range	20°C / 35°
Performance ambient temperature	25°
Notes	remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi
Customization options	Shapes, sizes, colour temperatures, RGB, RGBW
Net lamp weight	8,56 kg

Codes

PZRS1715G15NNE

Structure

black

PACKAGE

Package 01

Dimension: 155x155x5 cm / Gross weight: 1,25 kg

Certificazioni

