

ZIRKOL TRACK UGR

Nuova proposta della collezione, Zirkol Linear Track UGR è dotata di un particolare gruppo ottico che consente un'illuminazione diretta con ridotto indice di abbagliamento ($UGR < 19$), particolarmente adatta all'utilizzo in uffici e in ambienti di lavoro, dove è richiesto un elevato comfort visivo. Profilo in alluminio disponibile nelle finiture white e black e con temperatura colore LED di 3000K e 4000K. Zirkol Linear Track UGR è compatibile con binario 3C/0-10V. Driver on-board.



0,84M | 3000M

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2160lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54084I42NBO
BZRL54084I42NNE

Structure

white
black

Certificazioni



1,15M | 3000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2957lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54115I42NBO
BZRL54115I42NNE

Structure

white
black

Certificazioni



0,84M | 4000K

LAMPING

Source	LED strip
Total power	26W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2220lm
Typ CRI	>90
IP class	40
Dimensions	84x3,5x10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	


Codes

BZRL54084I42WBO
BZRL54084I42WNE

Structure

white
black

Certificazioni



1,15M | 4000K

LAMPING

Source	LED strip
Total power	35W
Emission	UGR<19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	3039lm
Typ CRI	>90
IP class	40
Dimensions	115x3,5,10cm
Materials	aluminium
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white compatible with TRACK 3C/0-10V length
Customization options	

Codes

BZRL54115I42WBO
BZRL54115I42WNE

Structure

white
black

Certificazioni

