

ZIRKOL LINEAR WALL

Dedicato ad un'illuminazione indiretta e dalla forte connotazione decorativa, Zirkol Linear Wall è la nuova lampada della collezione, proposta con una forma lineare e fissaggio a parete. Tre temperature colore LED disponibili, 2700K, 3000K o 4000K e finiture black, white e gold.



1M | 2700K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	833lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15DBO
BZRL4010G15DNE
BZRL4010G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M | 3000K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	882lm
Initial luminaire efficacy	61lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15WBO
BZRL4010G15WNE
BZRL4010G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



1M | 4000K

ZIRKOL LINEAR WALL

LAMPING

Source	LED strip
Total power	14,5W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	980lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	100x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	1,32 kg

Codes

BZRL4010G15NBO
BZRL4010G15NNE
BZRL4010G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 115x11x11 cm / Gross weight: 2,12 kg

Certificazioni



2M | 2700K

LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	1666lm
Initial luminaire efficacy	57lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15DBO
BZRL4020G15DNE
BZRL4020G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 250x11x11 cm / Gross weight: 4,69 kg

Certificazioni



ZIRKOL LINEAR WALL



2M | 3000K

LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	1764lm
Initial luminaire efficacy	61lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15WBO
BZRL4020G15WNE
BZRL4020G15WOR

Structure

white
black
gold

PACKAGE

Package 01	Dimension: 250x11x11 cm / Gross weight: 4,69 kg
------------	---

Certificazioni



ZIRKOL LINEAR WALL



LAMPING

Source	LED strip
Total power	29W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	1960lm
Initial luminaire efficacy	68lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	40
Dimensions	200x2,6x5cm
Materials	aluminium
Ambient temperature range	0°C / +35°C
Performance ambient temperature	25°C
Notes	included: 1 x driver Ultraslim 60W (220/240V) integrated driver RAL 9005 black RAL 9016 white length lumen output
Customization options	
Net lamp weight	2,69 kg

Codes

BZRL4020G15NBO
BZRL4020G15NNE
BZRL4020G15NOR

Structure

white
black
gold

PACKAGE

Package 01	Dimension: 250x11x11 cm / Gross weight: 4,69 kg
------------	---

Certificazioni

